

Flat Panel Ceiling Lifts—FPLCV2 +LM

FPLC V2+LM series of flat panel ceiling lift mechanisms offers vertical lowering motion, for applications with increased floor-ceiling distance.

Maximum safety is achieved in closed position with the electric safety locking system.

Its silent operation and smooth motion make this series an elegant and reliable solution!



Model	FPLCV2-42-50+LM+LOCK	FPLCV2-52-60+LM+LOCK
Maximum flat panel dimensions (WxHxD)	≤ 1280x755x90mm	≤ 1480x900x90mm
Maximum load (flat panel+ceiling cover)	45kg	
Lift dimensions (WxHxL), excluding control box	1630x250x1153mm	1795x250x1300mm
Vertical lowering distance up to	435mm	580mm
Mounting flat panel holes pattern up to	600x400mm	800x600mm
Standard color of metallic parts	powder coating in RAL 9005 black or RAL 9016 white	
Power supply	230VAC-50/60Hz	
Standard control option	dry contacts control box	
Optional controls	RF remote control, RS 232 or 485 ports	

ALL RIGHTS ARE STRICTLY RESERVED.

REPRODUCTION OR ISSUE TO 3RD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORIZATION BY UNITECH SYSTEMS
All above information may change by the manufacturer without prior notice or obligation of any kind.