



PLCV5 series of projector ceiling lifts — PLCV5.3 & PLCV5.4

The larger models of PLCV5 series, provide flexible and reliable solutions for almost every projector application.

Facilitating the installation with features like pre-drilled projector plate, cable chain for safe cable management, optional drop down ability (increase in number of scissor sets) available at ordering stage and accurate motion, PLCV5.3 & PLCV5.4 cover the needs of all regular projectors.



Model	PLCV5.3	PLCV5.3 +XD300	PLCV5.3 +2 x XD300	PLCV5.4	PLCV5.4 +XD500	PLCV5.4 +2 x XD500
Space inside carriage for projector (WxL)	555mm x 495mm			580mm x 707mm		
Maximum load capacity (projector+ceiling cover)	20kg			35kg		
Lift dimentions (WxD)	690mm x 596mm			720mm x 850mm		
Minimum required inner ceiling depth (height)	71mm +projector height	106mm +projector height	141mm +projector height	85mm +projector height	131mm +projector height	177mm +projector height
Vertical motion length	300mm	600mm	900mm	500mm	1000mm	1500mm
Cable management	cable chain					
Standard color	powder coating in RAL 9005 black					
Power supply	230VAC/50-60Hz					
Standard control option	wall switch over 230VAC/50-60Hz					
Optional controls	RF remote control, dry contacts control box, RS 232/485 control board ports (each one alternative to the other)					

ALL RIGHTS ARE STRICTLY RESERVED.

REPRODUCTION OR ISSUE TO 3RD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORIZATION BY UNITECH SYSTEMS

All above information may change by the manufacturer without prior notice or obligation of any kind.